





**AGM Longlife-series
10 years design life**



Nominal voltage	12 V	
Nominal Capacity 20HR,20°C):	135 Ah	
Internal resistance	Approx. 4.0 m Ω	
Maximum charging current	42.0 A	
Maximum discharge current	1400 A (5 sec.)	
Operating temperature range	-15°C 50°C	
Float use/ cycle use	13.5 - 13.8V/ 14.4 – 15.0V	
Expected life (20°C)	10 years in float (EUROBAT)	
Standard terminal	Threaded insert 8 mm	
Housing material	ABS	
Dimensions	length	344 mm (±2 mm)
	width	171 mm (±2 mm)
	height	280 mm (±2 mm)
Approx. Weight	45.5 kg	
Packing	1 pcs/box	


- Typical applications:**
- UPS and EPS systems
 - Computerized data bases
 - Life support equipment
 - Air traffic power stations
 - Security systems
 - Military base

- Valve Regulated Maintenance Free
- Absorbent Glassmat Technology
- Built to comply with DIN 43534, IEC896-2, BS6290-pt.4
- Low self discharge
- Classified as non- spillable and Non Dangerous goods by IATA, FAA, ADR, IMDG
- Can be discharged or stored in any position without leakage
- Cannot be charged while the terminal is downward.


Constant Current Discharge (Amperes) at 25 °C (77°F)																					
F.V/TIME	5min	10min	15min	20min	25min	30min	45min	50min	60min	90min	2h	3h	4h	5h	6h	7h	8h	9h	10h	12h	20h
1.85V/cell	210.0	163.8	137.8	122.2	108.0	100.3	78.2	72.5	66.9	50.4	43.3	32.6	26.7	22.5	19.7	17.4	15.8	14.5	13.6	11.6	7.24
1.80V/cell	244.3	187.4	154.7	135.1	118.3	109.0	84.4	78.2	70.6	53.8	46.6	35.0	28.4	23.8	20.8	18.4	16.6	15.1	14.0	12.0	7.49
1.75V/cell	279.0	212.9	174.4	149.3	129.5	118.4	92.0	85.3	77.0	57.1	48.4	36.4	29.3	24.4	21.5	19.0	17.2	15.5	14.4	12.3	7.68
1.70V/cell	315.7	240.4	193.4	164.8	142.1	129.3	99.1	91.0	81.5	60.3	51.0	38.3	30.7	25.8	22.5	19.8	17.9	16.2	14.9	12.7	7.88
1.65V/cell	338.8	258.2	207.1	175.4	150.5	136.5	104.9	96.3	84.3	62.4	52.9	39.9	31.9	26.6	23.3	20.5	18.5	16.7	15.3	13.0	8.12
1.60V/cell	377.8	284.0	226.8	190.5	161.9	145.6	109.0	100.1	86.8	64.1	54.3	40.9	32.6	27.2	23.8	20.9	18.8	17.0	15.7	13.3	8.25

Constant Power Discharge (Watts) at 25 °C (77°F)																					
F.V/TIME	5min	10min	15min	20min	25min	30min	45min	50min	60min	90min	2h	3h	4h	5h	6h	7h	8h	9h	10h	12h	20h
1.85V/cell	388.2	305.8	259.8	232.8	206.9	193.3	151.4	141.1	130.4	98.6	85.0	64.2	52.7	44.5	39.1	34.7	31.5	28.9	27.1	23.1	14.5
1.80V/cell	446.8	345.9	287.9	253.7	223.1	206.7	161.6	151.2	136.9	104.5	90.8	68.5	55.7	46.9	41.2	36.5	33.0	30.0	27.9	23.9	15.0
1.75V/cell	499.5	386.6	320.5	277.7	242.2	222.8	174.9	163.7	148.6	110.5	94.1	71.0	57.5	47.9	42.4	37.5	34.1	30.9	28.7	24.5	15.3
1.70V/cell	555.6	431.8	352.2	304.2	264.0	241.9	187.7	174.1	156.7	116.4	98.9	74.6	59.9	50.5	44.4	39.2	35.5	32.1	29.7	25.2	15.7
1.65V/cell	581.6	454.3	372.6	321.3	277.5	253.2	197.0	182.7	161.0	119.7	101.9	77.3	62.1	51.9	45.8	40.4	36.6	33.0	30.5	25.9	16.2
1.60V/cell	633.8	488.5	401.5	345.2	295.9	268.3	203.2	188.9	164.9	122.4	104.0	78.9	63.2	53.0	46.6	41.1	37.1	33.6	31.1	26.4	16.4


Charging characteristics




Discharge characteristics curves



Relationship between charging voltage and temperature



Cycle service life in relation to depth and discharge



Models available, Constant Power Discharge (Watts) at 25°C (77°F) 1.65V/c – Time, Weight

Model	5min	10min	15min	20min	25min	30min	50min	1h	1.5h	2h	4h	6h	8h	10h	20h	Weight
CPL 9 – 12L	53.4	37.8	29.1	24.2	20.9	18.0	11.9	10.6	7.63	6.19	3.73	2.69	2.11	1.76	0.93	2.75 kg
CPL 12 – 12	64.6	45.4	35.0	28.7	24.7	21.9	15.3	13.7	10.6	8.55	6.62	3.69	2.93	2.50	1.33	4.05 kg
CPL 18 – 12	96.9	68.0	52.6	43.1	37.1	32.8	23.0	20.6	15.9	12.8	7.97	5.54	4.40	3.75	1.99	6.0 kg
CPL 26 – 12	139.9	98.3	75.9	62.3	53.6	47.4	33.2	29.7	23.0	18.5	11.5	8.00	6.35	5.42	2.88	8.4 kg
CPL 28 – 12I	150.7	105.8	81.8	67.1	57.7	51.0	35.8	32.0	24.8	19.9	12.4	8.62	6.84	5.83	3.10	8.8 kg
CPL 28 – 12IA	150.7	105.8	81.8	67.1	57.7	51.0	35.8	32.0	24.8	19.9	12.4	8.62	6.84	5.83	3.10	9.5 kg
CPL 33 – 12*	294.3	197.0	149.6	122.2	104.1	90.1	60.3	51.9	36.8	29.0	15.6	11.1	8.67	7.39	3.82	11.7 kg
CPL 45 – 12I	187.0	146.0	119.8	103.3	89.2	81.4	58.7	51.7	38.5	32.8	19.9	14.7	11.8	9.81	5.20	14.5 kg
CPL 55 – 12I*	380.3	262.5	205.4	170.1	147.4	127.6	85.6	74.0	54.0	43.3	24.0	17.1	13.6	11.6	6.00	17.6 kg
CPL 65 – 12ID	270.1	210.9	173.0	149.2	128.8	118.8	84.8	74.7	55.6	47.3	28.8	21.2	17.0	14.2	7.51	21.0 kg
CPL 80 – 12	311.6	243.3	199.6	172.1	148.7	135.7	97.9	86.2	64.1	54.6	33.2	24.5	19.6	16.4	8.67	23.0 kg
CPL 100 – 12	415.5	324.5	266.2	229.5	198.2	180.9	130.5	115.0	85.5	72.8	44.3	32.7	26.1	21.8	11.6	32.0 kg
CPL 135 – 12	581.6	454.3	372.6	321.3	277.5	253.2	182.7	161.0	119.7	101.9	62.1	45.8	36.6	30.5	16.2	45.5 kg
CPL 150 – 12	623.2	486.7	399.2	344.2	297.3	271.3	195.8	172.5	128.3	109.2	66.5	49.0	39.2	32.7	17.3	48.2 kg
CPL 250 – 12	811.2	665.4	573.7	495.5	456.8	353.1	326.3	287.5	213.8	182	138	110.8	92.8	81.7	72.2 kg	

* High Rate