



CPXL 22-12

Extreme Cyclic battery
Dimensions (mm)

Standard terminal (mm)


Nominal voltage		12 V
Nominal capacity		22 Ah
Maximum charging current		11 A
Maximum discharge current		25 A
Maximum cycle life		1500 cycles
Operating temperature range		-10 C 60 C
Charge voltage		14.6V
Standard terminal		M5 + Powakaddy connection
Housing material		ABS
Dimensions	length	168 mm
	width	128 mm
	height	100 mm (1 mm)
Approx. Weight		3.0 kg
Packing		1 pc/box

Typical applications :

- Electric Vehicle
- Electric Wheelchairs
- E-bike
- Lawn mowers
- Golf-Carts
- Medical Equipment
- Boats

LiFePO4 Lithium Ferro battery
 High charging/discharging current
 Can be discharged, charged or stored in any position
 Cannot be connected in series because of internal PCM

Models available			
Model	Capacity (Ah)	Dimensions (mm)	Weight
CPXL 16 – 12	16	168 x 128 x 75	2.30 kg
CPXL 20 – 12	20	181.5 x 77 x 167.5	2.66 kg
CPXL 22 – 12	22	168 x 128 x 100	3.00 kg
CPXL 26 – 12	26	165 x 125 x 175	3.96 kg